

AMPLIFIER

Beats & Echo

MODULAR TILE

Construction	Tufted, Textured Loop
Tile Size	50 cm x 50 cm
Face Fiber	100% Universal® Nylon Type 6
Dye Method	Solution Dyed
Gauge	1/12
Stitches Per Inch	10
Tufts	120/in ² (1,858/100 cm ²)
Standard Backing	WellBAC® Function
Nominal Total Thickness	0.22" (5.60mm)
Nominal Total Weight	102.5 oz/yd ² (3,476 g/m ²)
Pile Thickness	0.11" (2.79 mm) nominal
Flammability (Radiant Panel Test)	CRF = 4.7kW/m ² ; Smoke = 114%. min
Antimicrobial	AlphaSan® AF Built-In Protection
Indoor Acoustic Properties (NRC or α W)	≥ 0.15 (Exceeds standard acoustic requirements)
Indoor Air Quality	Pass (ISO10580:2010)
ACCS Grading	Commercial Heavy Duty & Stairs (CHD 3*/REHD2 6*)
ECS Grading	Level 4 (Certificate No. 18006)
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia
Applicable Warranties	15-year Wear Warranty 15-year Dimensional Stability warranty 15-year Anti-Static Warranty 15-year Castor Chair Wear Warranty
Recommended Installation Method(s)	Beats & Echo (Quarter Turn, Monolithic) Echo (Random)



Ontera
A MILLIKEN COMPANY