## $Common \ Thread \ 2 \ ({\rm with \ WellBAC^{\,\rm M} \ Comfort})$

## MODULAR TILE

Construction Tile Size Yarn Type Stain Repel / Stain Resist / Soil Release Antimicrobial Dye Method Gauge Stitches Per Inch Tufts Standard Backing Recycled Content by Total Weight Nominal Total Thickness Nominal Total Weight Flammability (Radiant Panel Test) Lightfastness (AATCC 16E) Static Electricity (AATCC-134) 20% R.H.,70° F. Recommended Maintenance Indoor Air Quality–CRI Green Label Plus <sup>™</sup> VOC Texture Appearance Retention Rating Environmental Acoustic Rating Applicable Warranties	<pre>Millitron® 1/10 14.4 144/in<sup>2</sup> (2,230/100cm<sup>2</sup>) WellBAC<sup>™</sup> Comfort (non-reactive cushion backing) 26% Pre-Consumer 0.29" (7.5 mm) 103 oz/yd<sup>2</sup> (3,500 g/m<sup>2</sup>)</pre>
IVE: Site Related Solutions	Ontera Cushion backed tile + Non-Reactive Standard adhesive means install 90 days after a new concrete pour, fully warranted no testing required. Refer Ontera.com.au















Design Copyright - Milliken & Company

† (EU) No 528/2012 (BPR): Quattra-1240 Base contains AlphaSan® biocidal product (Zinc Pyrithione), to reduce the growth of bacteria, mold and mildew that can cause odours or staining.

This WellBAC™ cushion-back carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

