

# Nordic Stories

## Hidden Plains (Cushion)

MODULAR TILE

Construction	Tufted, Textured Loop
Tile Sizes	50cm x 50cm
Yarn Type	Universal® Fibers Solution-Dyed Nylon Type 6,6
Stain Repel / Stain Resist / Soil Release	StainSmart®
Antimicrobial	AlphaSan® AF Built-In Protection†
Dye Method	Solution Dyed
Tufted Face Weight	18.9 oz/yd <sup>2</sup> (641g/m <sup>2</sup> )
Gauge	1/12
Stitches Per Inch	10.4
Tufts	124.8/in <sup>2</sup> (1,933/100 cm <sup>2</sup> )
Finished Pile Height	0.101" (2.57 mm)
Standard Backing	Underscore™ ES Cushion
Recycled Content by Total Weight	ES Backing: 41.8% Pre-Consumer 0.0 Post Consumer, ESP Backing: 31.3% Pre-Consumer, 10.5% Post Consumer
Nominal Total Thickness	0.31" (7.9 mm)
Nominal Total Weight	100 oz/yd <sup>2</sup> (3,391 g/m <sup>2</sup> )
Flammability (Radiant Panel Test)	≥ 0.45 (Class I); Smoke = ≤ 450
Lightfastness (AATCC 16E)	≤ 4.0 at 80 Hours
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV
Recommended Maintenance	MilliCare® - Refer to the Ontera Cleaning & Maintenance guide or Millicare® Australia Pass (ISO10580:2010)
Indoor Air Quality	Commercial Extra Heavy Duty & Stairs (CEHDS)
ACCS Grading	Level 4 (Certificate 16108)
ECS Grading	15 year Wear Warranty
Applicable Warranties	15 year Dimensional Stability warranty 15 year Anti-Static Warranty 15 Year Castor Chair Wear Warranty
Recommended Installation Method(s)	Ashlar, Monolithic



**Ontera**  
A MILLIKEN COMPANY