

PRODUCT SPECIFICATIONS

Product Description

Textured Loop

Fibre

Nylon

Dye Method

Solution Dyed

Pile Weight

600 g/m² - 18 oz

Machine Gauge

1/12"

Pile Height

High 5mm to Low 3mm

Total Thickness

7.5mm

Backing

Thermoplastic

Tile Size

500mm x 500mm

Installation Method

Monolithic Ashlar Brick Quarter Turn



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive

Full floor coverage with low VOC pressure sensitive adhesive

Anti-Static Performance

AATCC 134 < 3.5kV

Dimensional Stability

< 0.2%

Fire Rating (AS/ISO 9239.1:2003)

Critical Radiant Flux 9.1 kW/m²

Area of Use

Contract Heavy Duty & Stairs

Antimicrobial

Zinc Oxide antimicrobial treatment

Stain Resistance

The Solution Dyed Nylon fibres have an added sulfonated nylon copolymer that renders the fibre chemically inert to acid dyes and stains.

Soil Resistance

The Solution Dyed Nylon fibres are treated with an advanced non-oil based technology low soil finish.

ENVIRONMENTAL CREDENTIALS

Environmental Management System

ISO 14001:2004 certified (IQNet)

Indoor Air Quality

VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.

Recycled Content

Minimum 30% recycled yarn content

Product Stewardship

Victoria Carpets, in partnership with our customer, will on a project by project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



ISO 9001:2008
ISO 14001:2004

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoria-carpet.com.au
www.victoriacarpets.com.au