



Product Specification

Soft Appeal

| | |
|---|--|
| Date: | July 2018 |
| Description: | Twist Pile |
| Pile Fibre: | Softmore Solution Dyed Nylon |
| Fibre Quality: | Multi-ply, Twisted and Heat Set |
| Gauge: | 2.54 mm (1/10") |
| Stitch Rate: | 50.0 per 100 mm |
| Pile Weight: | 2033 g/m ² (60 oz/yd ²) |
| Pile Height: | 12.0 mm |
| Colouration: | 100% Solution dyed |
| Primary Backing: | 112 g/m ² (3.3 oz/yd ²) heat stabilised woven polypropylene |
| Secondary Backing: | 203 g/m ² (5.7 oz/yd ²) woven jute |
| Laminate: | 948 g/m ² (28oz/yd ²) synthetic latex |
| Total Weight: | 12.1 kg / LM (97.3 oz/yd ²) |
| Width: | 3.66 metres. |
| ACCS Reg No: | 17026 |
| A.C.C.S. Grade: | Residential Extra Heavy Duty 2, Stairs – 6 star Contract Medium Duty, Stairs – 2 star |
| ACCS Environmental Classification Scheme: | ACCS Environmental Certification Level 3 |
| Critical Radiant Flux: (Burning Behaviour) | Conventionally laid on Airstep Steplux CRF Mean Result 3.6 kw/m ² SMOKE Value 371 % min |
| AS/ISO 9239-1:2003 Part 1 – Test | Conventionally laid on Dunlop Supergreen CRF Mean Result 3.7 kw/m ² SMOKE Value 339 % min |
| Slip Resistance: | Tested to AS 4586:2013 Mean SRV 64 Class P5 |
| Product Features: | * An exciting new range of super soft carpet, featuring exceptional colourfastness and stain resistance. |
| 20 Year Warranty: | * This Tuftmaster carpet is guaranteed against pile weight loss resulting from abrasive wear, where the carpet has been installed indoors in accordance with recommendations of the Australian Carpet Classification Scheme (ACCS). Provided that Tuftmaster Carpets is satisfied that the carpet was properly installed and maintained and that the surface pile has abrasively worn by more than 10% within twenty (20) years of installation, Tuftmaster Carpets will replace at its cost, the damaged area with same or similar carpet, inclusive of installation. |
| Colourfastness: | * With Softmore solution dyed nylon, Tuftmaster guarantees no significant colour change for twenty (20) years due to exposure to light or atmospheric contaminants. |
| Antistatic Protection: | * Unlike other carpets which are protected by topical treatment, Tuftmaster Softmore nylon filament has a permanent antistatic component that becomes an integral and durable part of the carpet thereby providing human protection from anti-static shock. |
| Quality Control: | *Soft Appeal has passed numerous tests to provide that integrity of construction, wear and colour performance that delivers a finished carpet quality assured for domestic use. |
| Notes: | *Seam Sealer to be used on all seams. *The use of chair pads is mandatory. *Must be laid in accordance with AS/NZ 2455.1:2007 *Subject to Tuftmaster's 'Terms of Trading'. |
| Colour Range: | *10 Colourways Aspen 101, Stone Beige 121, Atrium 131, Tawny Mist 141, Soft Camel 161, Dark Skies 921, Cauldron 951, Urban Grey 971, Torrent 991, Charcoal Ember 986. |

Please contact your Tuftmaster Representative for further information