Technical Data Sheet

Product Specifications





Product Details				
Technical Data		Technical Data		
Туре	Engineered Timber	Colours	10	
Plank Thickness	14mm	Finish	UV Matte	
Wear Layer	3.0mm	Surface	Brushed	
Dimensions	1900mm (L) x 190mm (W)	Profile	Round Edge	
Planks per Box	8	Substrate Layer	Plywood (FBE)	
M² per Box	2.888m²	Backing Layer	Hardwood Veneer	
Weight per box	27 Kg	Coating System	7 layers of UV Acrylic Lacquer	
M² per Pallet	115.52m²	Application	Commercial / Domestic	

Installation Method:

Glue-free patented clic locking system. Floating method preferred. Can be glued-down.

Performance				
Abrasion Rating	7 coats ≥ 6000 revolutions		ASTM D 4060-CS17	
Moisture Content	7% (+/- 2%) At time of delivery		EN 13183-1	
Reaction to Fire	Critical Radiant Flux 2.7 kW/m2 Smoke Value 21 %.min		AS/ISO 9239.1-2003	
Slip Resistance	R10 (for Fire Isolated Exits - Stairs)		DIN 51130:2014-02	
Impact Sound Insulation Rating Impact Sound Reduction	L'nT,w = 51 Δ L'nT,w = 15dB	200mm concrete slab & Timbermax	AS/NZS ISO140.7:2006	
Formaldehyde	< 0.01%	E1 (not detected)	EN 14342:2005+A1:2008	
Residential Warranty	20 Years (Wear Layer) & Lifetime (Structural)			
Sustainability				

Sustainability

VOC Rating CETEC and E1 compliant for VOC emission rate limits









