RUSTIC OAK

Engineered Timber







"Home is where the heart is"

For further information contact Customer Service on 1800 622 293 or visit www.heartridge.com.au

Updated 20-07-15



Built for strength and durability using a three layer construction, our Heartridge Engineered Oak comes backed with a lifetime residential structural guarantee.

Heartridge ensures your floors will remain beautiful for many years to come, always making your space a place to come home to.

Specifications - General				
Plank Size	Thickness	15mm		
	Veneer	3mm		
	Width	190mm		
	Length	1860mm		
Carton	2.12m ² - 6 Layers			
Nesting	1 Layer maximum. 630mm minimum.			
Weight per Carton	18kg			
Cartons per Pallet	50			
Structure	3mm veneer, pine core and poplar plywood			
	backing			
Veneer	Dry Sawn English Oak			
Coating	UV-cured urethane with Aluminium Oxide			
Surface Finish	Handscraped, matte finish			
Grading	Rustic (CDE)			
Edge	Micro Bevel			
Joining System	Tongue and Groove			
Installation Type	Glue-down, Nailed/Stapled, Floating			
Warranty	Structural	Lifetime Residential		
	Surface Finish	20 Years Residential		

Specifications - Technical		
Fire - Smoke	20% min	
Fire - CHF/CRF	4.4kW/m²	
Slip - Dry Floor Friction	D1	
Slip - Wet Pendulum	P3	
Slip - Oil Wet Ramp	R10	
Formaldehyde	E1	

Colour	Product Code	Barcode
Tawny Owl	820201	933992320201 9
White Smoke	820202	933992320202 6

Timber is a natural material and variations in colour, texture and presence of naturally occurring features are expected. Final product will exhibit variation from sample material. Timber flooring will react to direct sunlight, moisture and humidity in its environment and this must be managed by the homeowner.