

Woodland OAK

Engineered Timber



HEARTRIDGE

FLOORS BY DUNLOP



Showcasing the beauty of genuine European Oak, the veneers are wire brushed to emphasise the timber grain of the material, and constructed of a multi-layer plywood backing for optimal stability. Micro-bevelled edges and a matte-finish protective coating all work to create a timber floor that embraces the natural and raw aesthetic of the materials used.


A HeartrIDGE engineered timber floor will ensure that your space remains beautiful for many years to come.

Specifications - General

Plank Size	Thickness	14mm
	Veneer	3mm
	Width	190mm
	Length	1900mm
Carton Contents	2.888m ² - 8 Layers	
Nesting	2 Layers maximum. 500mm minimum.	
Weight per Carton	26.3kg	
Pallet Contents	40 cartons - 115.520m ²	
Structure	3mm veneer, multi-layer poplar & eucalyptus plywood backing	
Veneer	Dry Sawn English Oak (European Oak)	
Coating	UV-cured urethane with Aluminium Oxide	
Surface Finish	Brushed, matte finish	
Grading	Standard (ABC)	
Edge	Micro Bevel	
Joining System	Tongue and Groove	
Installation Type	Glue-down, Nailed/Stapled, Floating	
Warranty	Structural	Lifetime Residential
	Surface Finish	20 Years Residential



Specifications - Technical

Fire - Smoke	20% min	
Fire - CHF/CRF	4.4kW/m ²	
Slip - Dry Floor Friction	D1	
Slip - Wet Pendulum	P3	
Slip - Oil Wet Ramp	R10	
Formaldehyde	E1	
Raw Material Sourcing	FSC certified	

"Home is where the heart is"

For further information contact
Customer Service on 1800 622 293
or visit www.heartridge.com.au

Updated 30-10-17

Colour	Product Code	Barcode
Natural	820306	933992320306 1
Winter Cove	820307	933992320307 8
Foxtail	820309	933992320309 2

Timber is a natural material and variations in colour, texture and presence of naturally occurring features are expected. Final product will exhibit variation from sample material. Timber flooring will react to direct sunlight, moisture and humidity in its environment and this must be managed by the homeowner.