

TECHNICAL DATA SHEET

PRODUCT SPECIFICATION	STANDARD	EN ISO 10582
Vinyl Category		SPC Plank
Dimensions		1500 x 180mm
Total Thickness	EN ISO 24346	6mm
Wear Layer Thickness	EN ISO 24340	0.50mm
Usage Class	EN ISO 10874	Class 33 - AC5
Pack Size		1.62m ² (6 planks)
Pack Weight		16.5kg
Pallet Size		84.24m ² (52 packs)
Pallet Weight		890kg
Density	EN 436	2000kg/m ³
Surface Treatment		UV Coating (anti-bacterial)

PHYSICAL PROPERTY	TEST METHOD	SPECIFICATION
Dimensional Stability	EN ISO 23999	≤0.25%
Profile Strength	ISO 24334	≥ 5kN
Castor Chair Resistance	EN ISO 4918	No damage
Curling after exposure to heat	EN ISO 23999	≤ 1mm
Squareness & Straightness	EN 16511	≤ 400mm: ≤ 0.25mm ≥ 400mm: ≥ 0.35mm
Residual Indentation	EN ISO 24343-1	≤ 0.1mm
Light Fastness	EN ISO 105-B02	≥ 6
Impact Sound Reduction	EN ISO 10140-3	5 Star
Slip Resistance	EN 13893/DIN51130	DS / R10 / P2
Abrasion Group	EN660-2 EN 16511	Group T AC5 (0.50)
Peel Resistance	EN ISO 24345	60N/50mm
Fire Resistance	AS/ISO 9239.1-2003	9.4 kW/m ²
Thermal Resistance	EN 12667	0.017 (m ² K)/W
Electric Behavior	EN 1815	≤2KV
Indoor Air Quality		Low VOC (IAC GOLD certified)
Plasticizer		Ortho-phthalate free
Warranty	Domestic use	20 year wear warranty
	Commercial Use	Up to 15 years upon request

