

HYDROPLANK

NEW GEN WPC FLOORING

HYDROPLANK 5g CLICK FLOORING FOR FLOATING INSTALL

HYDROPLANK WPC flooring represents next generation manufacturing techniques utilising sustainable Wood Plastic Composites (WPC) to form a robust, interior waterproof flooring product.

The visual décors provide realistic embossed timber textures and colours in both Australian timber & classic Oak colour palettes to enhance modern interiors. The planks also display an attached acoustic foam layer that delivers excellent noise reduction capabilities. HYDROPLANK features a robust water based PU coating for everyday scuff resistance.

This next generation WPC flooring is dimensionally stable, highly durable and interior waterproof providing instant appeal for modern housing, retail and commercial shop fitout.

HYDROPLANK WPC FLOORING Valinge 5G Click 1830 x 228 & 178 x 7.6mm

| Colour | Scotia | Trim | Sqm/Ctn | Planks/Ctn | Ctns/Pallet | Micro Bevel |
|---------------------|-------------------|-------------|---------|------------|-------------|-------------|
| Bronx 228mm | Warm Springs | Lugano | 2.504m2 | 6 | 64 | Yes 4 sides |
| Brooklyn 228mm | Buckskin | Sunshine | 2.504m2 | 6 | 64 | Yes 4 sides |
| Chelsea 228mm | Twilight Mist | Rock | 2.504m2 | 6 | 64 | Yes 4 sides |
| Cooney Island 228mm | Barn Oak | Lugano | 2.504m2 | 6 | 64 | Yes 4 sides |
| Hamptons 228mm | Barn Oak | Lugano | 2.504m2 | 6 | 64 | Yes 4 sides |
| Harlem 228mm | Homestead | Brown | 2.504m2 | 6 | 64 | Yes 4 sides |
| Midtown 228mm | Barn Oak | Moon | 2.504m2 | 6 | 64 | Yes 4 sides |
| Queens 228mm | Crystal Lake | Rock | 2.504m2 | 6 | 64 | Yes 4 sides |
| Soho 228mm | Silvermoon | Snow | 2.504m2 | 6 | 64 | Yes 4 sides |
| Staten Island 228mm | Buckskin | Lugano | 2.504m2 | 6 | 64 | Yes 4 sides |
| Blackbutt 178mm | Coastal Blackbutt | Blackbutt | 1.920m2 | 6 | 85 | Yes 4 sides |
| Spotted Gum 178mm | NSW Spotted Gum | Spotted Gum | 1.920m2 | 6 | 85 | Yes 4 sides |

Key Features; Interior Waterproof, can be installed in wet areas including bathrooms and laundry. Valinge 5g click for easy install. WPC flooring provides a robust surface with good dimensional stability. Excellent for renovations over existing ceramic tiles, minimal telegraphing. High impact surface resistance. Super Width planks

Attached acoustic underlay to enhance walking comfort, warmth and minimise sound transmission.

Description & Profile; WPC construction. Valinge Patented 5g Click. Micro Bevel edges, V4.

Surface features; Embossed realistic timber visuals, colours and textures. Water based PU Matte coating.

Slip Rating; AS 4586:2013 Appendix A, Wet Pendulum P4. Australia

Fire Test; CHF Value 5.3Kw/m2. **Smoke Value** 220% min. **VOC Emissions;** < E1, **FloorScore Certified** SCS-EC10.3-2014 v3.0.



Preference Floors (NSW)

ABN 40 117 801 037
Unit A/31 Sturt Street,
Smithfield NSW 2164
t +61 2 9738 1188
f +61 2 9738 1199
sales@preferencefloors.com.au

Preference Floors (VIC)

ABN 34 151 422 927
19 Lanyon Street,
Dandenong South VIC 3175
t +61 3 9794 5111
f +61 3 9794 5133
vic@preferencefloors.com.au

Preference Floors (QLD)

ABN 81 169 158 990
6/268 Evans Road,
Salisbury QLD 4107
t +61 7 3875 1688
f +61 7 3875 1788
qld@preferencefloors.com.au

Preference Floors (SA)

ABN 63 600 454 215
47 Research Road,
Pooraka SA 5095
t +61 8 8262 2774
f +61 8 8359 4189
sa@preferencefloors.com.au

Preference Floors (WA)

ABN 25 625 850 455
30 King Street,
Bayswater WA 6053
t +61 8 9471 7785
f +61 8 9272 4906
wa@preferencefloors.com.au