Technical Data Sheet

Product Specifications





Product Poteile				
Product Details Technical Data			Technical Data	
Туре	Laminate	Laminate		6
Total Thickness	8.0mm	8.0mm		Ultra HDF / Melamine Resin
Wear Layer	Aluminium Oxide	Aluminium Oxide		Crystal
Dimensions	1215mm (L) x 194mm	1215mm (L) x 194mm (W)		Embossed
Planks per Box	10	10		Square Edge
M² per Box	2.3571 m ²	2.3571 m ²		141.426 m²
Veight per Box	16.5kg	16.5kg		Glue-free mechanical locking system
Performance				- System
Abrasion Resistance	AC3 / 23, 31			EN 13329
Impact Resistance	IC2	IC2		EN 13329
Resistance to staining	Group 1,2: Class 5	Group 1,2: Class 5		EN 438
Light Fastness	> Level 6 Blue Scale	> Level 6 Blue Scale		EN ISO 105-B02
Static Indentation	< 0.01mm - No visible	< 0.01mm – No visible Change		
Furniture Leg	No Change			EN 424
Castor Chair	No Change			EN 425
Thickness Swelling	≤ 18%			EN 13329-F
Reaction to Fire	Critical Radiant Flux Smoke Value	4.5 kW/m2 19 %.min	Conforms for all BCA Buildings	AS/ISO 9239.1-2003
Slip Resistance	P2, R9			AS/NZ 4586-2013
Impact Sound Insulation Rating Impact Sound Reduction	L'nT,w = 50 \triangle L'nT,w = $24dB$		230mm concrete slab & Timbermax	AS/NZS ISO140.7:2006
Formaldehyde	< 0.1%		E1 (not detected)	ENV717-1
Light Commercial Warranty	5 Years			
Residential Warranty	15 Years			
Sustainability				
VOC Rating	E1 compliant for VOC	E1 compliant for VOC emission rate limits		







