



## Integrated Warning & Directional Tactile

### Dome Dimensions

Top of Dome	25mm
Bottom of Dome:	35mm
Height of Dome	5mm

### Tactile Dimensions

Tactile Thickness	(Base) 3mm
Gap between Centre's	50mm
Square Meter Ratio (300mm x 300mm)	11 tiles per 1m <sup>2</sup>
Square Meter Ratio (400mm x 400mm)	6.25 tiles per 1m <sup>2</sup>

Range	Guardian Tactile Ground Surface Indicator – Warning and Directional Design
Material	Bayer Desmopan Polyurethane – High Grade and UV Resistant
Substrates	Concrete, Granite, Aggregate, Tiles, Vinyl, Rubber, Timber, Carpet
Installation	Integrated Warning/Directional Tactile Indicator - Adhesive-fixed Design
Standards	Complies with National Construction Code- Building Code of Australia D3.8 Manufactured to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 1428.4.1-2009 Complies to Australian Standards AS/NZS 4586-2013
Application	Peel, Bond and Walk® Technology
Warranty	Guaranteed for 10 Years

### Slip Resistant Testing

AS/NZS 4586-2004	OIL - WET Ramp Analysis	Mean overall acceptance angle = 22.9°	Class R11
AS/NZS 4586-2013	WET Pendulum Analysis	Slip Resistance Value (SRV) = 58	Class P5

### CSIRO Breaking Strength Testing

AS/NZS 4495.4-1997	Breaking Load (N)	Mean 16
AS/NZS 4495.4-1997	Breaking Strength (N)	Mean 15
AS/NZS 4495.4-1997	Modulus of Rupture (N/mm <sup>2</sup> )	Mean 9.79

### CSIRO Water Absorption Testing

AS/NZS 4459.3-1999	Water Absorption	20%
--------------------	------------------	-----

### Guardian Colour and Stock Codes

Colours	Application	Warning 300x300mm	Directional 300x300mm	Warning 400x400mm	Directional 400x400mm
Black	Internal and External	GTS3W-BK	GTS3D-BK	GTS4W-BK	GTS4D-BK
Warning Yellow	Internal and External	GTS3W-YL	GTS3D-YL	GTS4W-YL	GTS4D-YL
Terracotta	Internal and External	GTS3W-TR	GTS3D-TR	GTS4W-TR	GTS4D-TR
Medium Grey	Internal and External	GTS3W-MG	GTS3D-MG		
Colorado Grey	Internal only	GTS3W-CG	GTS3D-CG		
Ivory	Internal only	GTS3W-IV	GTS3D-IV	GTS4W-IV	GTS4D-IV