



## Integrated Fibre Reinforced Resin Polymer Plate

### Dome Dimensions

Top of Dome	25mm
Bottom of Dome:	35mm
Height of Dome	5mm

### Tactile Dimensions

Tactile Thickness	3mm
Gap between Centre's	50mm
Square Meter Ratio (600mm x 300mm)	5 tiles per 1m <sup>2</sup>
Countersunk Holes	8 Countersunk holes per plate

Range	Guardian Tactile Ground Surface Indicator- Surface Applied
Material	High Grade Fibre Reinforced Resin Polymer
Substrates	Concrete, Tiles, Vinyl, Rubber, Timber, Carpet
Standards	Complies with the National Construction Code D3.8 - Building Code of Australia Manufactured to Australian Standards AS/NZS 1428.4.1:2009 Complies to Australian Standards AS/NZS 1428.1:2009 Complies to Australian Standards AS/NZS 4586 - 2013
Warranty	Guaranteed for 5 Years

### Slip Resistant Testing

AS/NZS 4586:2004	OIL WET ramp	Class R12
AS/NZS 4586:2004	WET Pendulum	Class V

### Guardian Colour and Stock Codes

Colours	Application	Warning 600x300mm
Black	Internal and External	GTS600300-FRB
White	Internal and External	GTS600300-FRW
Yellow	Internal and External	GTS600300-FRY
Medium Gray	Internal and External	GTS600300-FRG

### Luminance Contrast

The National Construction Code of Australia and the AS/NZS 1428.4.1 require a minimum luminance contrast.  
Guidelines are as follows:

- Integrated tactile indicators – not less than 30%