


MODULAR LVT FLOORING

Profile



1. PUR Surface Protection
2. 0.55mm Wear Layer
3. Decor Layer
4. Base Layer
5. Fibreglass Core
6. Base Layer
7. Non-Slip Backing

Technical Specifications

Physical Properties

Wear layer	0.55mm
Thickness	5.0mm
Size	180mm x 1200mm
Qty per carton	8
M ² per carton	1.73m ²
Dura Coat surface treatment	Yes

Test Results

Test		Standard	Result
Classification	Heavy Domestic - Commercial	EN685	23/33/42
Residual indentation		EN ISO 24343-1	<0.1mm
Dimensional stability		EN ISO 23999	≤ 0.25%
Colourfastness to Light		ISO105-B02	≥6
Slip resistance	Oil wet ramp	AS/NZS4586	R9
	Wet pendulum	AS/NZS4586	P2
Reaction to fire	Critical radiant flux	AS/ISO9239-1	9.7 kW/M ²
	Smoke Value		97%min
Impact sound Reduction		ISO717-2	6dB
Recommended adhesive	Kenbrock SmartGrip		

Applications

- Domestic
- Commercial
- Retail
- Apartments
- Child & Aged Care
- Receptions
- Offices

Sustainability

Cushionwood makes environmental sense. It has low VOC and contains no heavy metal substances.

Cushionwood is manufactured in an ISO9001 and ISO14001 facility.

Features

- 5.0 mm plank thickness provides superior comfort cushioning underfoot and ensures less sound transfer
- 0.55mm Wear layer and PUR surface protection for easy maintenance
- Convenient modular 'drop down' floor laying
- Highly stable fibreglass core layer
- 20 year domestic warranty
- 7 year commercial warranty