

## 2017/2018 Luxury sheet vinyl flooring collection

CHARACTERISTIC	STANDARD	STYLE TX	APOLLO+	ARGO TX	LIFE TX	ULTRA TX	TOPAZ
THICKNESS mm	EN ISO 24364	2.10	2.40	2.20	2.80	3.20	2.50
WEAR LAYER mm	EN ISO 24340	0.20	0.35	0.25	0.35	0.50	0.70
WEAR LAYER TYPE	INTERNAL	SUPREME®	EXTREME®	EXTREME®	EXTREME®	EXTREME®	TOPCLEAN®
BACKING TYPE	INTERNAL	TX® FELT	PVC	TX® FELT	TX® FELT	TX® FELT	PVC
WEIGHT kg/m <sup>2</sup>	EN ISO 23997	1.490	1.730	1.590	1.880	2.220	2.900
ROLL SIZE m	EN ISO 24341	25	25	25	25	25	23
ABRASION CLASS	EN 660-2 EN 649	≤2mm <sup>3</sup> CLASS T	≤2mm <sup>3</sup> CLASS T	≤2mm <sup>3</sup> CLASS T	≤2mm <sup>3</sup> CLASS T	≤2mm <sup>3</sup> CLASS T	≤2mm <sup>3</sup> CLASS T
CASTER CHAIRS	ISO 4918 EN 425	NO	NO	NO	NO	NO	YES**
IMPACT SOUND	EN ISO 717/2	15dB	16dB	16dB	19dB	20dB	13dB
STATIC INDENTATION	EN ISO 24343-1	≤0.35mm	≤0.20mm	≤0.35mm	≤0.20mm	≤0.20mm	≤0.10mm
DIMENSIONAL STABILITY	EN ISO 23999	≤0.40%	≤0.40%	≤0.40%	≤0.40%	≤0.40%	≤0.40%
LIGHT FASTNESS	ISO 105/B02	≥6	≥6	≥6	≥6	≥6	≥6
THERMAL RESISTANCE	EN ISO 10456	0.03 m <sup>2</sup> /kW	0.06 m <sup>2</sup> /kW	0.03 m <sup>2</sup> /kW	0.04 m <sup>2</sup> /kW	0.06 m <sup>2</sup> /kW	NA m <sup>2</sup> /kW
SLIP RESISTANCE	EN 13893 DIN 51130	μ≥0.30 R10	μ≥0.30 R10	μ≥0.30 R10	μ≥0.30 R10	μ≥0.30 R10	μ≥0.30 R10
RECYCLABLE	INTERNAL TEST	NO	YES	NO	NO	NO	YES
CHEMICAL RESISTANCE	INTERNAL TEST	OK	OK	OK	OK	OK	OK
FIRE RATING	ISO 9239-1 CRF/%smoke	8.58/222	7.17/98	8.58/222	7.60/281	<i>In testing</i>	5.70/192
STATIC ELECTRICITY	EN 1815	≤2 kV	≤2 kV	≤2 kV	≤2 kV	≤2 kV	≤2 kV
PHTHALATE FREE	REACH	YES	YES	YES	YES	YES	YES
VOC EMISSIONS	INTERNAL TEST	<100 μg/m <sup>3</sup> After 28 days	<100 μg/m <sup>3</sup> After 28 days	<100 μg/m <sup>3</sup> After 28 days	<100 μg/m <sup>3</sup> After 28 days	<100 μg/m <sup>3</sup> After 28 days	<100 μg/m <sup>3</sup> After 28 days
FORMALDEHYDE	EN 14041:2004	E1	E1	E1	E1	E1	E1
WEAR CLASS DOMESTIC	EN ISO 10874	22	23	22	23	23	23
WEAR CLASS COMMERCIAL	EN ISO 10874	NA	NA	NA	NA	32	43
WARRANTY DOMESTIC	INTERNAL	10 YEARS	15 YEARS	15 YEARS	20 YEARS	20 YEARS	20 YEARS
WARRANTY COMMERCIAL	INTERNAL	NA	NA	NA	NA	5 YEARS#	10 YEARS#

\*\* MUST BE FULL STICK INSTALLATION WITH APPROVED CASTERS

# MUST BE FULL STICK INSTALLATION

